ALLEN&HEATH





SERVICE MANUAL

Publication AP5296

Introduction

This publication provides technical information on servicing the Allen & Heath **XONE:92**. Included are system block diagram, internal layout drawing and circuit schematics with board layouts. Whilst we believe this information to be reliable we do not assume responsibility for inaccuracies. We also reserve the right to make changes in the interest of further product development.

Additional Resources

Allen & Heath web site	www.allen-heath.com	Product information Technical downloads Distribution contacts Company contacts
Technical support	support@allen-heath.com	See web for local contact
Xone:92 user guide	AP5345	Operating instructions Performance specification User jumper link options

Xone:92 Service Information

Issue status: xone92_ap5296_3.doc

Print date: 04 November 2004

Copyright © 2004 Allen & Heath. All rights reserved

ALLEN&HEATH

Manufactured in the United Kingdom by Allen & Heath Kernick Industrial Estate, Penryn, Cornwall, TR10 9LU, UK http://www.allen-heath.com



Service personnel:	Service work should be carried out by technically qualified service personnel only. Mains power is dangerous and can kill. Do not attempt to work on a linear or switched mode power supply if you are not suitably qualified to do so. Do not attempt to repair surface mount circuit assemblies unless you are suitably qualified and have the necessary facilities to do so. Replacement circuit assemblies can be ordered.
Service facilities:	Ensure a suitably sized work surface is available. Ensure this is clear of dirt, debris and obstructions which may damage the equipment surfaces. Ensure adequate lighting. Use the correct tools for the job and ensure they are in good working order. Ensure all workshop safety requirements are adhered to.
Service information:	Check that you have all the information you need before starting the service job. Refer to the Allen & Heath web site or contact Allen & Heath technical support for details on the latest information. Full technical information can be downloaded from the web site Distributor Zone (password required).
Mains power:	Connect the equipment to mains power only of the type described in the user guide and marked on the rear panel. The power source must provide a good ground connection. Ensure you always use an isolation transformer when working on any mains power supply unit.
Mains cord and fuse:	Use the correct power cord as supplied with the equipment. Do not remove or tamper with the ground connection in the power cord. Heed the Important Mains Plug Wiring Instructions printed in the user guide if it is necessary to rewire the mains cord. Always replace the equipment mains fuse with the correct type and rating as described in the user guide and marked on the equipment panel.
Opening the unit:	Switch off and remove the mains power cord before opening the equipment. Ensure all power supply covers and safety shields are in place before applying power with the unit open for diagnostic fault finding.
Closing the unit:	Before finishing, check the quality and accuracy of the service work carried out. Remove any dirt or debris as this may cause equipment failure in the future. Ensure all assemblies, harnesses and connectors are correctly aligned and plugged in. Ensure that jumper settings and control configurations are correctly set according to the requirements of the customer.
Testing the unit:	Before operating the equipment, read and adhere to the Important Safety Instructions printed in the user guide. Test that the service work has been successfully carried out.
Shipping the unit:	Use adequate packing such as the original packaging or purpose designed flight case if you need to ship the unit. To avoid injury to yourself or damage to the equipment take care when lifting, moving or carrying the equipment.



User maintenance:	There are several user configurable jumper links inside. These are described in the user guide together with instructions on how to change the default settings.		
Technology:	The XONE:92 uses SMT (surface mount) PCB technology. In certain cases it may be better to replace a faulty assembly rather than try to fix it without the appropriate tools and training. The power supply is a built-in universal mains input, switched mode circuit which should be serviced by suitably qualified personnel only.		
Operation:	The XONE:92 is a performance club mixer. To ensure optimum performance and reliability it should be connected and operated as described in the user guide.		
Fault finding:	Refer to the system block diagram and circuit drawings to follow through the signal path during fault diagnosis. Replace suspected faulty components only with those specified by Allen & Heath. The use of lower grade alternatives may degrade the performance. Ensure the RCA phono insert jumper links are pressed fully in if fitted.		

Contents Log

XONE:92 – Historical Change Logxone92_ap5296_3.pdf
Removing the Top Panelxone92_top_panel_removal_1.pdf
Internal Layout drawingxone92_layout_1.pdf
Surface and Main Partsxone92_parts_2.pdf
Block Diagramxone92_blockdiagram_2.pdf
Stereo Fader PCB Assembly xone92_002-684_stereo_fader_3.pdf
Mic/Stereo Return PCB Assy xone92_003-136_mic_stereoreturn_2.pdf
Stereo Input PCB Assemblyxone92_003-137_stereo_3.pdf
Filter 1 & 2 PCB Assembly iss.2xone92_003-138_143_filter_2.pdf
Filter 1 & 2 PCB Assembly iss.3xone92_003-138_143_filter_3.pdf
Master PCB Assemblyxone92_003-139_master_2.pdf
Crossfader PCB Assemblyxone92_003-140_xfade_2.pdf
Slave PCB Assembly xone92_003-141_slave_2.pdf
Connector PCB Assembly xone92_003-142_connector_1.pdf
Linear Fader PCB Assemblyxone92_003-144_linear_fader_1.pdf
Rotary Fader PCB Assembly xone92_003-145_rotary_fader_2.pdf
PSU PCB Assembly
XONE:92 – Engineering Change Notesxone92_ecns_1.pdf

XONE:92 – Historical Change Log

The following list identifies historical changes to the **XONE:92**. The effective dates, serial numbers and related change note documentation are included for reference to help identify the correct issue circuit boards and components. Whilst we believe this information to be reliable we do not assume responsibility for inaccuracies. We also reserve the right to make changes in the interest of further product development.

Assembly	Description	From Serial Number	Date	Change Note Number
003-138/143	Filter 1 & Filter 2 iss.1 PCB mod	-	11/03/04	984
003-138/143 & 003-141	Filter value change + diode addition	060507	25/02/04	993
003-233	IEC Mains Filter with Nutserts	-	29/03/04	998
003-139	Master PCB output level change	063122	21/04/04	1018
003-141	Slave PCB capacitor change	063515	04/05/04	1020
User Guide	Issue 2 Block Diagram – Mix 1 output level changed from 0dBu to +4dBu	-	26/05/04	1026
003-138/143	Filter 1 & 2 PCBs up-issue to iss.3	064869	13/05/04	1036